



www.lynxpressuresystem.com

LEADER IN INDUSTRIAL
TRIPLEX PLUNGER PUMPS

Passionate about Providing Solutions

COMPANY PROFILE

We "Lynx Pressure System" situated at Ahmedabad (Gujarat, India) have gained acknowledgment in the field of manufacturing, exporting and importing an excellent range of PUMPS & PUMPING EQUIPMENT (i.e. Water Jet Pumps, Triplex Plunger Pumps, Hydro Pressure Test Pumps, Hydro Jetting Machines, etc.) We are Partnership firm established in the year 2011. Our well-established facility is spread over the vast land area and is further divided into well-functional units. These units are handled by our expert professionals who have vast experience in their particular domain.

Lynx Pressure System regularly supplies the High Pressure Pumps to major Government companies & PSUs viz. BHEL, National Institute of Rock Mechanics, SMBT, IIT-kanpur, Dubai Petroleum and many more. Also supplies to the blue-chip & renowned private buyers/users viz. Gujarat Fluoro chemicals Ltd, Magadh Sugar & Energy Ltd, Tata, L&T, Havmor, Vadilal, Torrent Power Ltd, Haldiram's, Chandan Steel Ltd, Hetero, Hyundai-dubai, GWELD, Sumeet Industries Ltd, Godrej, REPL, EPEPL, Motherson, Tejas Construction, Shivam Cement and many more i.e. consistently serving to nation's major core sectors for more than 9 years.


Lynx Pressure System' products are sold under popular & most reliable brand, " L Y N X ". These products are also designed and manufactured as per international standards. The range & type of L Y N X products are briefly listed below;

- Italy HAWK make Triplex Plunger Pumps ranging from 80 Bar to 500 Bar pressure
- L Y N X make High Pressure Pumps ranging up to 1400 Bar pressure
- High Pressure Accessories



PRODUCT RANGE

MAIN SERIES	MIN. LPM	MAX. LPM	MIN. PRESSURE BAR	MAX. PRESSURE BAR	MAX. POWER HP
HHP	8.5	70	50	500	40
BHF	51	139	50	180	40
BMP	22	55	125	500	40
BHP	5	20	400	1200	50
MP	35	145	150	1000	100
MF-HF	62	445	100	790	240
HP	42	70	880	1400	180



All the Pumps/Machines/Equipment are designed & manufactured for the ambient conditions and are capable to work and perform under any severe environment and for respective industry application. At shop floor, stringent quality control & measures are ensured at all the stages i.e. from incoming raw material stage to finish product, including painting & packing. To maintain the highest & best quality, it is ensured that the bought out items & components are fully tested and okayed at the respective suppliers' works & are also checked before fitted with the main equipment & tested at our works prior offered to the client. Thus making " L Y N X " a name synonymous and most promising with best quality and for better performance.


Ability to clean many times faster than conventional cleaning system to reduce breakdown time its helps to clean system without dismantling its saves precious time and money. "Eco Environmentally Process" since no hazardous chemicals involved.

INDUSTRY WE SERVE

- | | |
|---------------------------|----------------------------|
| ✓ Sugar Industry | ✓ Fertilizer Industry |
| ✓ Cement Industry | ✓ Oil & Gas Industry |
| ✓ Power Plant Industry | ✓ Distillery Industry |
| ✓ Chemical Industry | ✓ Food & Beverage Industry |
| ✓ Pharmaceutical Industry | ✓ Marine Industry |
| ✓ Petrochemical Industry | ✓ Tubes & Pipes Industry |
| ✓ Petroleum Industry | ✓ Pulp & Paper Industry |

OUR INFRASTRUCTURE

We have established an advanced infra structural unit that is spread over a wide area and is well-equipped with all the modern machines, tools, and equipment. To carry out a hassle free production process, we are bestowed with a state-of-the-art manufacturing facility. This unit is spread over a large area and has a massive installation capacity, that has enabled us in meeting bulk orders of our clients, within specified time schedule. Installed with hi-tech machines and tools, this unit assists us in manufacturing precision engineered products.



HHP SERIES

We offer a series of High-Pressure Hawk Italy Pumps. These are industrial high-pressure pumps, especially designed for the cleaning industry. HAWK name has been known for Quality, Reliability, Long Life & Nominal Maintenance. Every component of the pumps is carefully engineered. They are engineered & tested to meet stringent demands of the industry. With an excellent pressure range, they operate dependably.

BARE PUMP TECHNICAL SPECIFICATION

DESCRIPTION	SPECIFICATION
Pump Head	Forged Brass
Plungers	Ceramic Sleeve
Pump Main Body	Aluminium Di-Cast
Connecting Rod	Aluminium Di-Cast
Crank Shaft	Alloy Steel
Plunger Seal	Buna "N" Seal
Valve Assembly	SS 304
Oil	15W40



INDUSTRIES WISE APPLICATIONS

- **Food & Beverages:** Yeast, sediments and fermentation residues on vats, pipes and facilities.
- **Cement Plants:** Remove dirt, grease and product build up on grates, floors, external piping, bins, walls, hopper cars and handling equipment.
- **Construction:** Exposing aggregate (retarded). Asphalt distributors, mixers, tar cookers and pavers, Asphalt, dirt, concrete, mortar, tar, grease, mastic and clay on vehicles, mixer trucks and machinery,
- **Sewage Cleaning:** Cleaning of Reservoirs and containers, sewers and drain pipes, sanitation equipment and refuse vehicles.
- **Pulp & Paper:** Cleaning of grease, oil, pitch, dirt and wood pulp from heat exchangers, tubes, foundries, press sections of paper machines, suction rolls, stock chests and lines.
- **Mining:** Unclog plant machinery due to deposits of coal, rock dust, mud or oils.
- **Earth Moving Equipment:** Cleaning of Dumpers, Trucks, JCB, backhoe, excavator, loader, bulldozers, shovels, motor grader, motor scraper, heavy haul trucks, draglines, and trencher.

MODEL SELECTION CHART

Pump Models	Min. LPM	Max. LPM	Min. Pressure (Bar)	Max. Pressure (Bar)	Max. Power HP
NHD	8.5	14	60	200	7.5
NPM	15	18	120	250	15
NMT	18	21	150	200	10
NLT	25	30	125	250	15
PXI	11	21	250	500	30
XLT	18	55	100	300	25
XXT	42	70	120	200	30
MPX	25	30	350	500	40

BHF SERIES


High Pressure Triplex Plunger Pump is reciprocating positive displacement pumps. Triplex Plunger Pumps are used widely for creation of high flow of fluid under immense pressure.

Lynx Pressure System are Manufacturers of Pulley Belt Driven High-Flow Medium Pressure Triplex Water Pumps with pressure up to 180 BAR; 139 LPM flow rate.

Plunger Pumps are precision engineered to be used in diverse industry verticals. Offered in standard and customized forms, these Triplex Water Pumps are known for their resilience and dimensional accuracy.

BARE PUMP TECHNICAL SPECIFICATION

DESCRIPTION	SPECIFICATION
Pump Head	Forged SS304 / 316
Plungers	T.C. coated / Colmonoy Coating
Main Body	High Graded Casting
Connecting Rod	S. G. Iron
Crank Shaft	S. G. Iron
Plunger Seal	PTFE Aramide
Valve Assembly	PH 17-4
Stroke	40 MM
Max. Inlet Pressure	2-3 Bar
Oil Capacity	4 Ltrs
Weight	60 Kgs
Inlet Ports	1/2"
Discharge	3/4"
Oil	80W40



INDUSTRIES WISE APPLICATIONS

- ▶ **R. O. Plant:** Reverse Osmosis
- ▶ **Water Treatment Plant:** Water Treatment
- ▶ **Tubes & Pipes:** Hydro Testing for cross country pipelines, Valves, etc.
- ▶ **Municipal Corporation:** Sewer Jetting (Drain line cleaning)

MODEL SELECTION CHART

Pump Models	SPM	Flow (LPM)	Max. Rated Pressure-kg/cm ² (MOTOR-HP)		
BHF30	950	80	180 (40)	130 (30)	80 (20)
	730	61	180 (30)	-	-
	610	51	180 (25)	130 (20)	-
BHF32	950	91	150 (40)	125 (30)	100 (25)
	730	70	150 (30)	125 (25)	100 (20)
	610	58	150 (25)	125 (20)	98 (15)
BHF36	950	115	120 (40)	99 (30)	80 (25)
BHF40	730	110	100 (30)	75 (25)	50 (15)
BHF45	730	139	100 (40)	75 (30)	50 (20)

BMP SERIES

Triplex Plunger Pumps are precision engineered to be used in diverse industry verticals. Offered in standard and customized forms, these Triplex Water Pumps are known for their resilience and dimensional accuracy.

High Pressure Plunger Pumps are Reciprocating Positive Displacement Pumps.

Triplex High-Pressure Plunger Water Pumps are used widely for creation of high flow of fluid under immense pressure.

BARE PUMP TECHNICAL SPECIFICATION

DESCRIPTION	SPECIFICATION
Pump Head	Forged SS 304 / 316
Plungers	T.C. coated / Colmonoy Coating
Main Body	High Graded Casting
Connecting Rod	S. G. Iron
Crank Shaft	S. G. Iron
Plunger Seal	PTFE Aramide
Valve Assembly	PH 17-4
Stroke	40 MM
Max. Inlet Pressure	2-3 Bar
Oil Capacity	4 Ltrs
Weight	60 Kgs
Inlet Ports	3/4"
Discharge	1/2"
Oil	80W40



INDUSTRIES WISE APPLICATIONS

- **Aviation:** Expansion joints, grease, rubber and hydraulic fluids on runways.
- **Highway Maintenance:** Graffiti, stains, tar and mastics on concrete bridges and overpasses. Removal of expansion joints and paint strips.
- **Marine:** Removal of marine growth, barnacles, loose paint and rust on ship hulls, docks, ballasts, platforms, storage tanks and boilers, Underwater cleaning pipes and drilling platforms, of barnacles and marine growth to 'white metal'.
- **Mining:** Pre-maintenance cleaning of dumpers, drag lines, underground haulage lines and shafts; aids in the recovery of ore.
- **Pharmaceutical:** Cleaning of chemicals (liquid and solids) from pipes, kettles, mixers, tubes, heat exchangers, reactors, filters and evaporators.
- **Railway & Earth moving Machinery:** Removal of leaf mulch from railway lines.
- **Cement Plants:** Cooler hearths and pre-heater columns, bins, hopper cars, floors, rotary kilns and walls.
- **Chemical Processing:** Chemicals from boiler tubes, tanks, valves, evaporators, heat exchangers, tube bundles, pipes, vessels, reactors and facilities.

MODEL SELECTION CHART

Pump Models	SPM	Flow (LPM)	Max. Rated Pressure-kg/cm2 (MOTOR-HP)			
BMP18	950	30	500 (40)	360 (30)	315 (25)	270 (20)
	730	22	480 (30)	400 (25)	320 (20)	-
BMP20	950	35	390 (40)	300 (30)	245 (25)	195 (20)
	730	27	380 (30)	315 (25)	250 (20)	190 (15)
BMP22	950	43	320 (40)	240 (30)	200 (25)	160 (20)
	730	33	320 (30)	260 (25)	210 (20)	160 (15)
BMP25	950	55	240 (40)	190 (30)	155 (25)	125 (20)

BHP SERIES

High Pressure Triplex Plunger Pumps are used widely for creation of heavy flow of fluid under immense pressure. Triplex Plunger Pumps use three Plungers, which reduces the pulsation of single reciprocating plunger pumps.

Lynx Pressure System are Manufacturers of Ultra High-Pressure Pumps BHP Series with pressure up to 1200 BAR; 20 LPM flow rate. Plunger Pumps are reciprocating positive displacement pumps.

BARE PUMP TECHNICAL SPECIFICATION

DESCRIPTION	SPECIFICATION
Pump Head	Forged SS 304 / 316
Plungers	T.C. coated / Colmonoy Coating
Main Body	High Graded Casting
Connecting Rod	S. G. Iron
Crank Shaft	S. G. Iron
Plunger Seal	PTFE Aramide
Valve Assembly	PH 17-4
Stroke	40 MM
Max. Inlet Pressure	2-3 Bar
Oil Capacity	4 Ltrs
Weight	60 Kgs
Inlet Ports	3/4"
Discharge	1/2"
Oil	80W40



INDUSTRIES WISE APPLICATIONS

- ▶ **Aviation:** Expansion joints, grease, rubber and hydraulic fluids on runways.
- ▶ **Railway & Earth moving Machinery:** Removal of leaf mulch from railway lines.
- ▶ **Mining:** Pre-maintenance cleaning of dumpers, drag lines, underground haulage lines and shafts; aids in the recovery of ore.
- ▶ **Power Plants:** Industrial Tube Cleaning (i.e. Heat Exchanger, Evaporators).
- ▶ **Tubes & Pipes:** Hydrostatic Pressure Testing.
- ▶ **General Manufacturing:** High Pressure Water Jet Cleaning.

MODEL SELECTION CHART

Pump Models	SPM	Flow (LPM)	Max. Rated Pressure-kg/cm2 (MOTOR-HP)			
BHP12	730	9	1200 (30)	1000 (25)	800 (20)	600 (15)
	540	7	1200 (25)	1000 (20)	800 (15)	600 (12.5)
	420	5	1200 (20)	1000 (15)	800 (12.5)	600 (10)
BHP14	730	13	1000 (40)	800 (30)	600 (25)	400 (15)
BHP16	730	17	750 (40)	600 (30)	500 (25)	-
	950	20*	1000 (50)	-	-	-

MP SERIES

Triplex Plunger Pumps are Reciprocating Positive Displacement Pumps. Triplex Pumps use three plungers, which reduces the pulsation of single reciprocating plunger pumps.

High Pressure Water Pumps are used widely for creation of heavy flow of fluid under immense pressure. Plunger Pumps are precision engineered to be used in diverse industry verticals. Offered in standard and customized forms, these pumps are known for their resilience and dimensional accuracy.

BARE PUMP TECHNICAL SPECIFICATION

DESCRIPTION	SPECIFICATION
Pump Head	Forged SS 410
Plungers	Ceramic Sleeve
Main Body	High Graded Casting
Connecting Rod	S. G. Iron
Crank Shaft	Forged EN-24
Gear Box	Hardened & Teeth Grounded Helical Gear & Pinion Shaft
Plunger Seal	PTFE Aramide
Valve Assembly	PH 17-4
Oil	SAE 320
Stroke	75 MM
Max. Inlet Pressure	2-3 Bar
Oil Capacity	7 Ltrs
Weight	140 Kgs
Inlet Ports	2"
Discharge	1/2"



INDUSTRIES WISE APPLICATIONS

- ▶ **Automobile:** Paint from booths, machinery, gratings, conveyers, dollies and skids.
- ▶ **Cement Plants:** Cooler hearths and pre-heater columns, bins, hopper cars, floors, rotary kilns and walls.
- ▶ **Chemical Processing:** Evaporators, heat exchangers, tube bundles, pipes, vessels, reactors and facilities.
- ▶ **Highway Maintenance:** Graffiti, stains, tar and mastics on concrete bridges and overpasses. Removal of expansion joints and paint strips. Unblock culverts on bridges and clean up overspills.
- ▶ **Marine:** Removal of marine growth, barnacles, loose paint and rust on ship hulls, docks, ballasts, platforms, storage tanks and boilers, Underwater cleaning pipes and drilling platforms, of barnacles and marine growth to 'white metal'.
- ▶ **Metal Working:** Mill scale, tight rust and weld slag from new vessels, tanks and pipes.
- ▶ **Oil Refineries:** Water scale, coke, hard carbons and polymers in heat exchangers, pipes, tubes and tanks.
- ▶ **Petrochemical:** Calcium carbonate and sulphate, chlorides, hard polymers, iron oxide, coke, hard carbon, PVC and PVA on heat exchangers and reboilers.
- ▶ **Pharmaceutical:** Cleaning of chemicals (liquid and solids) from pipes, kettles, mixers, tubes, heat exchangers, reactors, filters and evaporators.
- ▶ **Power Plant:** Cleaning of Nuclear decontamination of fuel capsules, 'U' tube exchangers, flash from pre-heater tubes, hand tools and equipment.
- ▶ **Surface Preparation:** Removal of Paint, rust, refractory build-up, salts, concrete on surface.

MODEL SELECTION CHART

Pump Models	SPM	RPM	Flow (LPM)	MAX. RATED PRESSURE kg/cm ² 60 HP	75 HP	100 HP
MP3575P	530	1500	35	620	750	1000
MP4580P	530	1500	45	500	625	840
MP5270P	530	1500	52	430	530	720
MP6260P	530	1500	62	360	450	600
MP7050P	530	1500	70	310	375	510
MP8045P	530	1500	80	270	330	450
MP9040P	530	1500	90	240	300	400
MP11530P	530	1500	115	190	230	315
MP14525P	530	1500	145	150	185	250

MF SERIES

Triplex Plunger Pumps are used widely for creation of heavy flow of fluid under immense pressure. This Triplex Plunger Pump uses three pistons, which reduces the pulsation of single reciprocating piston pumps.

Plunger Pumps are precision engineered to be used in diverse industry verticals. Offered in standard and customized forms, these pumps are known for their resilience and dimensional accuracy.

BARE PUMP TECHNICAL SPECIFICATION

DESCRIPTION	SPECIFICATION
Pump Head	Forged SS 410
Plungers	Ceramic Sleeve
Main Body	High Graded Casting
Connecting Rod	S. G. Iron
Crank Shaft	Forged EN-24
Gear Box	Hardened & Teeth Grounded Helical Gear & Pinion Shaft
Plunger Seal	PTFE Aramide
Valve Assembly	PH 17-4
Oil	SAE 320
Stroke	105 MM
Max. Inlet Pressure	2-3 Bar
Oil Capacity	8 Ltrs
Weight	220 Kgs
Inlet Ports	3"
Discharge	1/2"



INDUSTRIES WISE APPLICATIONS

- ▶ **Aluminium:** Hardened Bauxite dust on mills, filters, floors, tanks, sumps and sewers.
- ▶ **Cement Plants:** Cooler hearths and pre-heater columns, bins, hopper cars, floors, rotary kilns and walls.
- ▶ **Chemical Processing:** Chemicals from boiler tubes, tanks, valves, evaporators, heat exchangers, tube bundles, pipes, vessels, reactors and facilities.
- ▶ **Construction:** Latence for canals, lifts, dams and runways prior to pours (no retarders). Exposing aggregate (unretarded) and concrete cutting.
- ▶ **Food Processing:** Grease, fats, oils, dirt and dough, food residues from vats, ovens, mixers, conveyors and facilities.
- ▶ **Oil Refineries:** Water scale, coke, hard carbons and polymers in heat exchangers, pipes, tubes and tanks.
- ▶ **Petrochemical:** Calcium carbonate and sulphate, chlorides, hard polymers, iron oxide, coke, hard carbon, PVC and PVA on heat exchangers and reboilers.
- ▶ **Pharmaceutical:** Cleaning of chemicals (liquid and solids) from pipes, kettles, mixers, tubes, heat exchangers, reactors, filters and evaporators.
- ▶ **Power Plant:** Cleaning of Nuclear decontamination of fuel capsules, 'U' tube exchangers, flash from pre-heater tubes, hand tools and equipment.
- ▶ **Railway & Earth moving Machinery:** Cleaning of Gypsum, potash, cement, lime in container cars; removing grease, dirt and deposits from trucks, undercarriages and tank cars, Removal of leaf mulch from railway lines.

MODEL SELECTION CHART

Pump Models	SPM	RPM	Flow (LPM)	MAX. RATED PRESSURE kg/cm ²		
				100 HP	120 HP	150 HP
MF24	435	1500	62	655	790	-
MF26	435	1500	73	560	670	770
MF28	435	1500	84	485	580	665
MF30	435	1500	97	420	505	580
MF32	435	1500	110	370	445	505
MF36	435	1500	139	285	340	400


HF SERIES

Triplex Plunger Pumps are used widely for creation of heavy flow of fluid under immense pressure. This Triplex Plunger Pump uses three Pistons, which reduces the pulsation of single reciprocating piston pumps.

Plunger Pumps are precision engineered to be used in diverse industry verticals. Offered in standard and customized forms, these pumps are known for their resilience and dimensional accuracy.

BARE PUMP TECHNICAL SPECIFICATION

DESCRIPTION	SPECIFICATION
Pump Head	Forged SS 410
Plungers	Ceramic Sleeve
Main Body	High Graded Casting
Connecting Rod	S. G. Iron
Crank Shaft	Forged EN-24
Gear Box	Hardened & Teeth Grounded Helical Gear & Pinion Shaft
Plunger Seal	PTFE Aramide
Valve Assembly	PH 17-4
Oil	SAE 320
Stroke	105 MM
Max. Inlet Pressure	2-3 Bar
Oil Capacity	8 Ltrs
Weight	220 Kgs
Inlet Ports	3"
Discharge	1/2"



INDUSTRIES WISE APPLICATIONS

- **Municipal Corporation:** Sewer Jetting (Drain line cleaning)
- **Tubes & Pipes:** Hydro Testing for Cross country pipeline
- **R.O. Plant:** Reverse Osmosis
- **Metal Industry:** Metal Powder Process
- **Steel Industry:** Descaling

MODEL SELECTION CHART

Pump Models	SPM	RPM	Flow (LPM)	MAX. RATED PRESSURE kg/cm ²		
				100 HP	120 HP	150 HP
HF40	435	1500	172	225	270	325
HF45	435	1500	218	175	210	255
HF50	435	1500	269	145	170	205
HF55	435	1500	326	120	140	170
HF60	435	1500	367	100	120	145

HP SERIES

Triplex Ultra High-Pressure Pumps are reciprocating positive displacement pumps.

Ultra High-Pressure Pumps use three plungers, which reduces the pulsation of single reciprocating plunger pumps.

High Pressure Plunger Pumps are used widely for creation of heavy flow of fluid under immense pressure.

Plunger Pumps are precision engineered to be used in diverse industry verticals. Offered in standard and customized forms, these pumps are known for their resilience and dimensional accuracy.

BARE PUMP TECHNICAL SPECIFICATION

DESCRIPTION	SPECIFICATION
Pump Head	Forged SS 410
Plungers	Ceramic Sleeve
Main Body	High Graded Casting
Connecting Rod	S. G. Iron
Crank Shaft	Forged EN-24
Gear Box	Hardened & Teeth Grounded Helical Gear & Pinion Shaft
Plunger Seal	PTFE Aramide
Valve Assembly	PH 17-4
Oil	SAE 320
Stroke	105 MM
Max. Inlet Pressure	2-3 Bar
Oil Capacity	8 Ltrs
Weight	220 Kgs
Inlet Ports	3"
Discharge	1/2"



INDUSTRIES WISE APPLICATIONS

- ▶ **Chemical Processing:** Chemicals from boiler tubes, tanks, valves, evaporators, heat exchangers, tube bundles, pipes, vessels, reactors and facilities.
- ▶ **Oil Refineries:** Water scale, coke, hard carbons and polymers in heat exchangers, pipes, tubes and tanks.
- ▶ **Petrochemical:** Calcium carbonate and sulphate, chlorides, hard polymers, iron oxide, coke, hard carbon, PVC and PVA on heat exchangers and reboilers.
- ▶ **Pharmaceutical:** Cleaning of chemicals (liquid and solids) from pipes, kettles, mixers, tubes, heat exchangers, reactors, filters and evaporators.
- ▶ **Power Plant:** Cleaning of Nuclear decontamination of fuel capsules, 'U' tube exchangers, flash from pre-heater tubes, hand tools and equipment

MODEL SELECTION CHART


Pump Models	SPM	RPM	Flow (LPM)	MAX. RATED PRESSURE kg/cm ²			
				100 HP	120 HP	150 HP	180 HP
HP42140P	500	1500	42	900	1000	1400	-
HP52110P	500	1500	52	-	880	1100	-
HP70100P	500	1500	70	-	-	-	1000

HIGH PRESSURE PUMPS ACCESSORIES

We, Lynx Pressure System are providing up to 1400 Bar High Pressure Triplex Plunger Pumps & Equipment Accessories for Car Washing, General Cleaning, Hydro Testing, Hydro Jetting & Blasting, Tube Cleaning etc.

High Pressure Cleaning Nozzles

Degree Nozzles



Variable Spray Angle Nozzle



Surface Cleaning Nozzle



Rotating Nozzle



Tube Cleaning Nozzle



Special Cleaning Nozzle



High Pressure Trigger Operated Gun

ITALY
MAKES
IMPORTED
Pressure
up to
250 Bar



ITALY
MAKES
IMPORTED
Pressure
up to
500 Bar



Unloader Valve

ITALY
MAKES
IMPORTED
Pressure
up to
350 Bar



ITALY
MAKES
IMPORTED
Pressure
up to
500 Bar



Pressure Regulating Valve

Italy makes imported
Pressure up to 250 Bar



Italy makes imported
Pressure up to 350 Bar



LYNX makes
Pressure up to 500 Bar



LYNX makes
Pressure up to 1400 Bar



High Pressure Dump Gun

Max. Flow
up to 80 LPM
Max. Pressure
up to 1500 Bar



Safety Valve

Italy makes
imported
Pressure
up to 250 Bar



Italy makes
imported
Pressure
up to 350 Bar



LYNX
makes
Pressure
up to
500 Bar



Foot Operated Valve (FOV)

LYNX makes - Max. Pressure up to 1400 Bar



High Pressure Water Blaster Hose

Polyhose / Parker makes - Max. Pressure up to 1400 Bar



Glycerine Filled Pressure Gauge

700 Bar



1000 Bar



2100 Bar



High Pressure Flexible Lance

Nominal Size :
M7, 4mm, 6mm
Pressure :
350 Bar - 1500 Bar



High Pressure SS Rigid Lance

Nominal Size:
1/2", 1/4", 3/8"
Length:
300mm - 2000mm



Sand Blasting Attachment

Max. Pressure
up to 500 Bar



Valves

High Pressure Ball Valve



Non Return Valve



OUR VALUABLE CLIENTS



DOMESTIC NETWORK



OUR GLOBAL **NETWORK**



LYNX PRESSURE SYSTEM

- 📍 Survey No. 242/3, FP-2/3, Plot No. 2, Panchratna Industrial Estate, Nr. Ramol Bridge, Ramol, Ahmedabad - 382445, Gujarat, India.
- ☎ Sales Dep.: +91-9909983982, +91-9978974666
- ✉ sales@lynxpressuresystem.com
- 🌐 www.lynxpressuresystem.com

